



Product Data Sheet

MOTOR OIL VX 0W-30

Product Description:

MOTOR OIL VX 0W-30 is a high performance fuel saving LOW SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed.

MOTOR OIL VX 0W-30 is formulated with high quality synthetic base stocks (PolyAlphaOlefine) in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

MOTOR OIL VX 0W-30 meets the following performance criteria:

ACEA C3 VW 504 00 / 507 00

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15°C	kg/m ³	ASTM D4052	844
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	61,9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12,3
Viscosity Index		ASTM D2270	203
Viscosity CCS @-35°C, max	cP	ASTM D2270	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45
Total Base Number	mgKOH/g	ASTM D2896	8.0
Sulphated Ash	%Wt	ASTM D874	0.7

Product Nr: 4529

Date Issued: 20-03-2018

Date Superseded: -

Revision nr: -