Product Data Sheet

MOTOR OIL SL 15W-40

Product Description:

MOTOR OIL SL 15W-40 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

MOTOR OIL SL 15W-40 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.

MOTOR OIL SL 15W-40 exceeds the following performance criteria:

ACEA A3/B3 MB 229.1 VW 505.00 API SL/CF

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	15W-40
Density@15°C	kg/m^3	ASTM D4052	879
Kin. Viscosity @40°C	mm^2/s	ASTM D7042	86
Kin. Viscosity @100°C	mm^2/s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	143
Viscosity CCS @-20°C, max	cP	ASTM D2270	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.5
Sulpated Ash	%Wt	ASTM D874	1.05

Product Nr: 4208	Date Issued: 15-01-2018	Date Superseded: 17-03-2017	Revision nr: 03

77 Lubricants B.V.
Van Ewijckskade 1G – 1761 JA Anna Paulowna, The Netherlands
www.77lubricants.nl; e-mail: info@77lubricants.nl