



**Product Data Sheet**

**MOTOR OIL SL/CF 10W-40**

**Product Description:**

**MOTOR OIL SL/CF 10W-40** is an universal high performance semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

**MOTOR OIL SL/CF 10W-40** is formulated with high quality re-refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

**MOTOR OIL SL/CF 10W-40** exceeds the following performance criteria:

API SL/CF

| Properties                | Unit               | Test Method | Typical Value |
|---------------------------|--------------------|-------------|---------------|
| SAE Grade                 |                    | SAE J3000   | 10W-40        |
| Density@15°C              | kg/m <sup>3</sup>  | ASTM D4052  | 863           |
| Kin. Viscosity @40°C      | mm <sup>2</sup> /s | ASTM D7042  | 99            |
| Kin. Viscosity @100°C     | mm <sup>2</sup> /s | ASTM D7042  | 15.2          |
| Viscosity Index           |                    | ASTM D2270  | 161           |
| Viscosity CCS @-25°C, max | cP                 | ASTM D2270  | 7000          |
| Flash Point COC           | °C                 | ASTM D92    | >201          |
| Pour Point                | °C                 | ASTM D7346  | -36           |
| Total Base Number         | mgKOH/g            | ASTM D2896  | 6.8           |
| Sulphated Ash             | %Wt                | ASTM D874   | 0.95          |

Product Nr: 4209

Date Issued: 15-01-2018

Date Superseded: 17-03-2017

Revision nr: 04