



Product Data Sheet

MOTOR OIL SF 15W-40

Product Description:

MOTOR OIL SF 15W-40 is a multi functional mineral engine oil for older gasoline-, diesel- and LGP engines of passenger car and light vans with or without turbo compressor. MOTOR OIL SF 15W-40 is not suited for engines equipped with a Diesel Particle Filter (DPF).

MOTOR OIL SF 15W-40 is formulated with special selected base stocks in combination with unique additive package to reach the following properties:

- Stable viscosity index.
- Good protection against rust, corrosion and wear.
- Good dispergency and detergency properties.
- Good antifoam properties.

MOTOR OIL SF 15W-40 exceeds the following performance criteria:

API SF/CD

| Properties | Unit | Test Method | Typical Value |
|---------------------------|--------------------|-------------|---------------|
| SAE Grade | | SAE J3000 | 15W-40 |
| Density@15°C | kg/m ³ | ASTM D4052 | 879 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 105 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 14.0 |
| Viscosity Index | | ASTM D2270 | 135 |
| Viscosity CCS @-20°C, max | cP | ASTM D2270 | 7000 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -30 |
| Total Base Number | mgKOH/g | ASTM D2896 | 5.0 |
| Sulphated Ash | %Wt | ASTM D874 | 0.66 |

Product Nr: 4212

Date Issued: 15-01-2018

Date Superseded: 16-03-2015

Revision nr: 02