



Product Data Sheet

MOTOR OIL ASP 5W-30

Product Description:

MOTOR OIL ASP 5W-30 is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a PSA B71 2290 specification is required and suitable for all engines which require an C2 performance specification.

MOTOR OIL ASP 5W-30 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

MOTOR OIL ASP 5W-30 exceeds the following performance criteria:

API SN/CF ACEA C2 Renault RN 0700 PSA B 71 2290 Fiat 9.55535-S1

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	5W-30
Density@15°C	kg/m ³	ASTM D4052	852
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	64
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.1
Viscosity Index		ASTM D2270	166
Viscosity CCS @-30°C, max	cP	ASTM D2270	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	7.7
Sulphated Ash	%Wt	ASTM D874	0.8

Product Nr: 4232

Date Issued: 16-01-2018

Date Superseded: 08-06-2015

Revision nr: 04