



MOTOR OIL SL 20W-50

Product Description:

MOTOR OIL SL 20W-50 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

MOTOR OIL SL 20W-50 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

MOTOR OIL SL 20W-50 meets the following performance criteria:

ACEA A3/B3

MB 229.1

VW 505.00

API SL



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density@15°C	kg/m ³	ASTM D4052	884
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	152
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	17.8
Viscosity Index		ASTM D2270	130
Viscosity CCS @-15°C, max	cP	ASTM D5293	6660
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	8.7
Sulphated Ash	%Wt	ASTM D874	1.06

Product Nr: 42100

Date Superseded: 15-01-2018

Date Issued: 10-12-2019

Revision nr: 03