



# MOTOR OIL ASP 5W-30

## Product Description:

**MOTOR OIL ASP 5W-30** is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a PSA B71 2290 specification is required and suitable for all engines which require an C2 performance specification.

**MOTOR OIL ASP 5W-30** is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

**MOTOR OIL ASP 5W-30** meets the following performance criteria:

**API SN/CF**

**ACEA C2**

**Renault RN 0700**

**PSA B 71 2290** > until 2017

**Fiat 9.55535-S1**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	856
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	61.5
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	10.6
Viscosity Index		ASTM D2270	163
Viscosity CCS @-30°C, max	cP	ASTM D5293	5550
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	7.8
Sulphated Ash	%Wt	ASTM D874	0.8

**Product Nr:** 42320

**Date Superseded:** 16-01-2018

**Date Issued:** 10-12-2019

**Revision nr:** 04