



MOTOR OIL RN 5W-30

Product Description:

MOTOR OIL RN 5W-30 is a high performance fuel saving LOW SAPS oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans specially designed for the latest generation Renault and Nissan diesel engines equipped with a Diesel Particulate Filter (DPF) and all other engines where an ACEA C4 product is required.

MOTOR OIL RN 5W-30 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extend oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

MOTOR OIL RN 5W-30 meets the following performance criteria:

ACEA C4

Renault RN0720

MB 226.51



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	70
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.3
Viscosity Index		ASTM D2270	174
Viscosity CCS @-30°C, max	cP	ASTM D5293	<5300
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.0
Sulphated Ash	%Wt	ASTM D874	≤0.5

Product Nr: 42330

Date Superseded: 19-02-2018

Date Issued: 10-12-2019

Revision nr: 05