



MOTOR OIL HM 10W-40

Product Description:

MOTOR OIL HM 10W-40 is a universal performance semi synthetic oil for use in older (1995-2010) gasoline- and diesel engines of passenger car and light vans with or without turbocharger specially formulated to help demands of "High-Mileage" engines which have been running for more than 100.000 km.

This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF) and not intended for vehicles predating 1990 that need increased zinc/phosphorus (ZDDP) oils.

MOTOR OIL HM 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Maximize the life of the engine.
- Special formulated additive helps to stop/reduce small oil leaks on seals.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level + high viscosity index

MOTOR OIL HM 10W-40 exceeds the following performance criteria:

ACEA A3/B4-08 API SL/CF

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density@15°C	kg/m ³	ASTM D4052	864
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.6
Viscosity Index		ASTM D2270	156
Viscosity CCS @-25°C, max	cP	ASTM D2270	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	7.1
Sulphated Ash	%Wt	ASTM D874	0.95

Product Nr: 42390

Date Superseded: 13-12-2017

Date Issued: 10-12-2019

Revision nr: 01

