



MOTOR OIL 20W-50

Product Description:

MOTOR OIL 20W-50 is a universal high performance engine oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL 20W-50 is formulated with high quality hydro-treated mineral base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL 20W-50 meets the following performance criteria:

API SN/CF

ACEA A3/B4

MB 229.1/229.3

VW 501.01/505.00



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density@15°C	kg/m ³	ASTM D4052	865
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	139
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	18.3
Viscosity Index		ASTM D2270	147
Viscosity CCS @-15°C, max	cP	ASTM D5293	3890
Flash Point COC	°C	ASTM D92	>215
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	10.4
Sulphated Ash	%Wt	ASTM D874	1.31

Product Nr: 42400

Date Superseded: 16-01-2018

Date Issued: 10-12-2019

Revision nr: 03