



THERM OIL 32

Product Description:

THERM OIL 32 is a premium quality heat transfer oil intended for use in closed indirect heating systems with expansion tanks temperatures up to 315°C and for open heating systems provided that the oil temperature does not exceed 180°C

THERM OIL 32 is based on high quality mineral base oil to ensure the following properties:

- Excellent thermal and oxidation stability.
- Minimizes deposit formation and viscosity increase.
- Extended service life and reduced downtime.
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well up to a maximum bulk oil temperature of 315°C with minimal interference with heat transfer capability.
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation.
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local over-heating.
- Non corrosive to aluminium, steel, copper, brass or bronze.
- Non-toxicity of this oil provides easy disposal of used oil.



Property	Unit	Test Method	Typical Value
ISO VG Grade		ISO 3448	32
Density@15°C	kg/m ³	ASTM D4052	868
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.3
Viscosity Index		ASTM D2270	101
Flash Point COC	°C	ASTM D92	230
Fire Point	°C	ISO 2592	250
Pour Point	°C	ASTM D7346	-15
Initial Boiling Point	°C	ISO 3771	>355
Auto Ignition Temperature	°C	DIN 51794	>360
Total Acid Number	mgKOH/g	ASTM D974	< 0.05

Product Nr: 43890

Date Superseded: 16-07-2013

Date Issued: 18-12-20191

Revision nr: 03