



GAS ENGINE OIL ZA 15W-40

Product Description:

GAS ENGINE OIL ZA 15W-40 is a premium quality heavy-duty ashless natural gas engine oil specially developed for lubrication of high performance, turbo-charged, 2-stroke gas engines requiring “ashless” oil.

GAS ENGINE OIL ZA 15W-40 is based on a high quality virgin mineral base oils in combination with a special selected additive package to obtain the following properties:

- Excellent thermal-, nitration-, and oxidation stability.
- Very effective in controlling carbon and ash deposits in combustion chamber and on exhaust and intake ports.
- Minimize ring scuffing.
- Controls carbon and ash deposits minimizing port plugging in two cycle engines and keeps spark plugs clean.

GAS ENGINE OIL ZA 15W-40 exceeds the following performance criteria:

Ajax **Superior** **Cooper** **Clark**
Dresser-Rand

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density@15°C	kg/m ³	ASTM D4052	887
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	96
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	145
Flash Point COC	°C	ASTM D92	>240
Pour Point	°C	ASTM D7346	-24
Total Base Number	mgKOH/g	ASTM D2896	1.2
Sulphated Ash	%Wt	ASTM D874	<0.01

Product Nr: 44560
Date Superseded: 27-08-2012

Date Issued: 17-12-2019
Revision nr: 04

