



# FLUSHING OIL 32

## Product Description:

**FLUSHING OIL 32** is a high quality effective oil to flush gasoline- and diesel engines. FLUSHING OIL is very effective in between switching from a low quality oil to a higher quality oil. It is also suitable to clean out the used engine oil if it is contaminated with moisture, coolant, fuel and/or engine sludge.

**FLUSHING OIL 32** is based on high quality base oil, in combination with special additive to obtain the following properties.

- High dispersant and detergent properties.
- Good resistance against corrosion.
- Mixable with mineral and synthetic multigrade engine oils.
- Good emulsification and neutralization properties.
- Good antiwear, anticorrosion and antifoam properties.



Property	Unit	Test Method	Typical Value
ISO VG Grade		ISO 3448	ISO 32
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	864
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	5.8
Viscosity Index		ASTM D2270	32
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-21
Total Base Number	mgKOH/g	ASTM D2896	2.4

**Product Nr:** 45120

**Date Superseded:** 01-08-2015

**Date Issued:** 18-12-2019

**Revision nr:** 01