



MOTOR OIL SEMI-SYNTH 5W-30

Product Description:

MOTOR OIL SEMI-SYNTH 5W-30 is an universal high performance fuel saving oil based on semi-synthetic technology for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL SEMI-SYNTH 5W-30 is formulated with high quality mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL SEMI-SYNTH 5W-30 meets the following performance criteria:

API SN/CF

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	61.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10.7
Viscosity Index		ASTM D2270	166
Viscosity CCS @-30°C, max	cP	ASTM D5293	4600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	7.0
Sulphated Ash	%Wt	ASTM D874	1.26

Product Nr: 45210

Date Superseded: 20-06-2017

Date Issued: 13-12-2019

Revision nr: 01

