



# MOTOR OIL SYNTHETIC 0W-30

## Product Description:

**MOTOR OIL SYNTHETIC 0W-30** is a high performance fully synthetic motor oil for gasoline- and diesel engines of modern passenger cars and light vans with or without turbo-charger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

**MOTOR OIL SYNTHETIC 0W-30** is formulated with high quality 100% synthetic base oil (Poly Alpha Olefin (PAO)) in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

**MOTOR OIL SYNTHETIC 0W-30** meets the following performance criteria:

**API SL  
MB 229.5**

**ACEA A3/B4-16  
Renault RN 0700/0710**

**VW 502.00/505.00  
VCC 95200356**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-30
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	844
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	68.7
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	12.3
Viscosity Index		ASTM D2270	180
Viscosity CCS @-35°C, max	cP	ASTM D5293	6010
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51
Total Base Number	mgKOH/g	ASTM D2896	10
Sulphated Ash	%Wt	ASTM D874	1.51

**Product Nr:** 42190

**Date Superseded:** 04-05-20187

**Date Issued:** 10-12-2019

**Revision nr:** 05